


Camera tracking discussing digital conference system

GS-350



- With LCD windows in both main controller and speaking unit
- Easy to realize camera tracking without connecting PC
- Build-in feedback suppressor
- System includes FIFO(first in first out), LIFO(late in first out), auto mode, discussing mode and chairman mode etc
- It supports PELCO P/D, YAAN and SONY EVI-D70 camera agreement. Any other agreements can be downloaded under special requirement.
- AUX output and line output to fulfill external audio equipment, such as recorder
- Tel in and Tel out for telephone coupler to realize remote conference
- RS-232 connectors for video switch and central controller
- With 4 channels output, and each channel can support utmost 40 units. Up to 160 units in total
- Supporting 4 chairman units



GS-350M

GS-350M Specification

Max current consumption	1A
Sensitivity	-15dB
Frequency response	50Hz-20KHz
S/N ratio	81dB

Line out level	11dB
Balance out level	11dB
Tel in level	-15dB
Dimension	483*323*90mm



- Professional and elegant plastic base
- Red ring indicator shows the active unit
- Built-in loudspeaker
- Hyper directional gooseneck microphone
- With volume adjustment
- With priority button in chairman unit to override all the delegate units



GS-350C

Design patent : ZL 2010 3 0181855.1
ZL 2005 3 0068726.0

GS-350D



GS-350C/GS-350D Specification

Earphone jack	3.5mm jack
Cable connector	DIN 8 Pins
Power supply	DC24V supplied by main controller
Max current consumption	60mA
Sensitivity	-50dB/Pa
Frequency response	100Hz-15KHz
S/N ratio	70dB
Directional pattern	Hyper cardioid



GS-350 System connection

